

## Medium-Mu Twin Triode

### CONTROLLED HEATER WARM-UP TIME

The 8CG7 is the same as the 6CG7 except for the following items:

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . . .	8.4	volts

## Medium-Mu Dual Triode

With Dissimilar Units

### CONTROLLED HEATER WARM-UP TIME

The 8CM7 is the same as the 6CM7 except for the following items:

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . . .	8.4	volts

## Twin Diode—High-Mu Triode

### CONTROLLED HEATER WARM-UP TIME

The 8CN7 is the same as the 6CN7 except for the following items:

Heater Characteristics and Ratings:

Heater-section arrangement	Parallel	Series	Series	
Voltage (AC or DC). . . . .	4.2 <sup>a</sup>	8.4 <sup>b</sup>	8.4 ± 0.8	volts
Current. . . . .	0.450 ± 0.030	0.225 ± 0.010	0.225 <sup>c</sup>	amp

<sup>a</sup> At 0.450 ampere.

<sup>b</sup> At 0.225 ampere.

<sup>c</sup> At 8.4 volts.

