


TUNG-SOL

DIODE

COMPACTRON

OUTLINE DRAWING

JEDEC 9-60



BASE 12 PIN BUTTON
JEDEC E12-70


FOR TV DAMPING
DIODE APPLICATIONS

COATED UNIPOTENTIAL CATHODE

ANY MOUNTING POSITION

BASING DIAGRAM

JEDEC 12 GA



BOTTOM VIEW

BASING DIAGRAM
JEDEC 12 GA

SOCKET TERMINALS 5, 6, 8 AND 9
SHOULD NOT BE USED AS TIE POINTS.
IT IS FURTHER RECOMMENDED THAT
THE SOCKET CLIPS FOR
THESE PINS BE REMOVED.

THE 6BE3A IS A COMPACTRON, SINGLE HEATER-CATHODE TYPE DIODE INTENDED FOR SERVICE AS THE DAMPING DIODE IN THE HORIZONTAL DEFLECTION CIRCUIT OF TELEVISION RECEIVERS. EXCEPT FOR HEATER CHARACTERISTICS AND RATINGS, THE 6BE3A IS IDENTICAL TO THE 12BE3A AND THE 17BE3A. THE VOLTAGE DROP OF THIS TYPE IS LOWER THAN THAT OF THE 6BE3.

DIRECT INTERELECTRODE CAPACITANCES - APPROX.
WITHOUT EXTERNAL SHIELD

CATHODE TO PLATE AND HEATER: K TO (P + H)	10	pf
PLATE TO CATHODE AND HEATER: P TO (K + H)	8.0	pf
HEATER TO CATHODE: (H TO K)	3.4	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD R5-239

AVERAGE CHARACTERISTICS	6.3	VOLTS	1200	MA
HEATER SUPPLY LIMITS:				
VOLTAGE OPERATION - AC OR DC			6.3 ± 0.6	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE:				
HEATER NEGATIVE WITH RESPECT TO CATHODE				
DC COMPONENT			900	VOLTS
TOTAL DC AND PEAK			5000	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE				
DC COMPONENT			100	VOLTS
TOTAL DC AND PEAK			300	VOLTS

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

TV DAMPER SERVICE SEE BELOW

PEAK INVERSE PLATE VOLTAGE	5000	VOLTS
PLATE DISSIPATION	6.5	WATTS
STEADY STATE PEAK PLATE CURRENT	1200	MA
DC OUTPUT CURRENT	200	MA

FOR OPERATION IN A 525-LINE, 30-FRAME SYSTEM AS DESCRIBED IN 'STANDARDS OF GOOD ENGINEERING PRACTICE FOR TELEVISION BROADCASTING STATIONS; FEDERAL COMMUNICATIONS COMMISSION'. THE DUTY CYCLE OF THE VOLTAGE PULSE MUST NOT EXCEED 15 PERCENT OF ONE SCANNING CYCLE.

AVERAGE CHARACTERISTICS

TUBE VOLTAGE DROP, $I_b = 350$ MA. DC	22.5	VOLTS
---------------------------------------	------	-------