

10LE8

Twin Dual-Control Pentode

The 10LE8 is the same as the 6LE8 except for:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 10 | V |
| Warm-up time (Average). | 11 | s |

11AR11

Semiremote-Cutoff Twin Pentode

DUODECAR TYPE

The 11AR11 is the same as the 6AR11 except for:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 11.2 | V |
| Warm-up time (Average). | 11 | s |

11CY7

Dual Triode

With High-Mu Unit and Low-Mu Unit

The 11CY7 is the same as the 6CY7 except for:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 11.0 | V |
| Warm-up time (Average). | 11 | s |

11DS5

Beam Power Tube

The 11DS5 is the same as the 6DS5 except for:

Heater Characteristics and Ratings

| | | |
|---|---------------|---|
| Current | 0.450 ± 0.030 | A |
| Voltage (AC or DC) at 0.450 A | 11.2 | V |
| Warm-up time (Average). | 11 | s |