

# 17CT3

## Half-Wave Vacuum Rectifier

9-PIN MINIATURE TYPE  
For TV Damper Service

The 17CT3 is the same as the 6CT3 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	16.8	V
Warm-up time (Average) . . . . .	11	s

# 17CU5

## Beam Power Tube

7-PIN MINIATURE TYPE

The 17CU5 is the same as the 6CU5 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	16.8	V
Warm-up time (Average) . . . . .	11	s

# 17D4

## Half-Wave Vacuum Rectifier

For TV Damper Service

The 17D4 is the same as the 6DA4 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A . . . . .	16.8	V
Warm-up time (Average) . . . . .	11	s

# 17DE4

## Half-Wave Vacuum Rectifier

For TV Damper Service

The 17DE4 is the same as the 6DE4 except for the following items:

### Heater Characteristics and Ratings

Current . . . . .	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A . . . . .	17	V
Warm-up time (Average) . . . . .	11	s