

1K3/1J3

Half-Wave Vacuum Rectifier

Electrical:

Filament Characteristics and Ratings:

	Min.	Av.	Max.	
Voltage (AC)	1.05	1.25	1.45	volts
Current at 1.25 volts.	-	0.2	-	amp
Direct Interelectrode Capacitance (Approx.): ^a				
Plate to filament and internal shield		1.6		pf

Mechanical:

Operating Position	Any
Type of Cathode	Coated Filament
Maximum Overall Length	3-9/16"
Seated Length	2-13/16" ± 3/16"
Maximum Diameter	1-9/32"
Bulb	T9
Cap.	Small with Tubular Support (JEDEC No. C1-34)

Bases (Alternates):

Intermediate-Shell Octal:


6-Pin, Arrangement 1 (JEDEC Group 1, No. B6-8)

Short Intermediate-Shell Octal with External Barriers:

6-Pin, Arrangement 1 (JEDEC Group 1, No. B6-60)

Basing Designation for BOTTOM VIEW 3C

- Pin 1 - See Note
- Pin 2 - Filament
- Pin 3 - See Note
- Pin 5 - See Note
- Pin 7 - Filament,
Internal Shield
- Pin 8 - See Note
- Cap - Plate



NOTE: May be used only under conditions specified in Operating Considerations.

PULSED-RECTIFIER SERVICE

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^b

Inverse Plate Voltage:		
Total dc and peak ^c	26000 max.	volts
DC	22000 max.	volts
Peak Plate Current	50 max.	ma
DC Plate Current	0.5 max.	ma

Characteristics:

DC Plate Voltage	225	volts
DC Plate Current	7	ma



1K3/1J3

- a Without external shield.
- b As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.
- c The duration of the voltage pulse must not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

OPERATING CONSIDERATIONS


Socket Connections. Socket terminals 1, 3, 4, 5, 6, and 8 may be connected to socket terminal No. 7 or to a corona shield which is connected to socket terminal 7. Socket terminals 4 and 6 may be used as tie points for components at or near filament potential.

Measurement of Filament Voltage. To measure the filament voltage when the filament is at a high dc potential with respect to ground, it is recommended that a simple method utilizing visual comparison of the filament temperature be used. The color temperature of the filament, operating from a pulse-or-rf-power source, may be checked by observing in a darkened room the reflection of the incandescent filament upon the surface of the internal shield. A visual comparison of this color temperature with that obtained when the filament of another 1K3/1J3 is operated from a dc or low-frequency ac supply of 1.25 volts, provides a convenient means for adjusting the amount of excitation to produce 1.25 volts (rms) at the filament terminals.

The high voltages at which the 1K3/1J3 is operated are very dangerous. Great care should be taken in the design of apparatus to prevent the operator from coming in contact with these high voltages. Particular care against fatal shock should be taken in the measurement of filament voltage. Under all circumstances, circuit parts which may be at high potentials should be enclosed or adequately insulated.


X-radiation. The voltages employed in some television receivers and other high-voltage equipment are sufficiently high that high-voltage rectifier tubes may produce X-radiation which can constitute a health hazard unless such tubes are adequately shielded. Relatively simple shielding should prove adequate, but the need for this precaution should be considered in equipment design.

1K3/1J3



DIMENSIONS IN INCHES

AVERAGE PLATE CHARACTERISTIC



92CS-10251



RADIO CORPORATION OF AMERICA
 Electronic Components and Devices
 Harrison, N. J.

DATA 2
 3-64